



### Product Specifications

KV3eco is a thermosetting plastic material reinforced with glass fiber. High-quality raw materials and a special manufacturing process give **KV3eco** its exceptional characteristics.

### Material Specifications:

- Long-term resistance to temperature and pressure
- Excellent dimensional stability
- No risk of delamination

### Fields of Application

**KV3eco** combines excellent insulating properties with exceptional dimensional stability, even when subjected to extreme loads and stresses.

It is installed on heated presses and used as an insulator for molds.

### Supply Details:

- **Standard Thickness:** 5-30 mm
- **Premium Finish Available**

The values in this technical data sheet are standard values and are not part of any contract. Specifications may change depending on modifications in the operating environment.



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.

**Planichem s.r.l.**

Via Consolare 41/43 25030 Zocco di Erbusco (BS) - ITALY

Tel: +39 030 7386033 - [www.planichem.com](http://www.planichem.com) - [info@planichem.com](mailto:info@planichem.com)