



**SICHEM® S93** is a **biaxially oriented modified microcellular PTFE gasket sheet filled with mica**, a mineral-based filler known for its **high heat resistance, excellent dielectric strength, and outstanding chemical stability**.

The **multidirectional molecular structure** and the **mica-based filler** provide the material with **excellent mechanical performance**, superior **resistance to hot creep**, and **optimal thermal and dimensional stability**, even under **prolonged loads**.

**High chemical and high-temperature resistance:** mica is resistant to many chemical agents, making it suitable for operation in **corrosive environments**, including exposure to **solvents and oxidizing agents**. PTFE cannot be used with **molten alkali metals, elemental fluorine (F<sub>2</sub>), or fluorinated gases**. PTFE is not compatible with: **bromine trifluoride, chlorine trifluoride, fluorine dioxide, hydrogen fluoride, molten alkali metals, elemental lithium, elemental potassium, and elemental sodium**. For compatibility with the filler materials used in the SicheM range, please refer to the **Chemical Compatibility List**.

**Superior mechanical stability:** the biaxial orientation improves resistance to **creep and permanent deformation**.

**Excellent machinability:** easy to **punch and CNC cut**, ensuring precision even for complex geometries.

**Low permeability coefficient:** ideal for applications requiring **long-term tight sealing**.

**Operating temperature:** from **-200°C to +260°C**, depending on the type of fluid and the applied load.

Bidirectional PTFE	SicheM S93
Composition	Microcellular Modified PTFE with mica
Density ASTM F 1315	1.2 g/cm <sup>3</sup>
Minimum operating temperature	-260 °C
Maximum operating temperature	+260 °C
Max operating pressure	50 bar
P x T Max. ( Thk 0.8 - 2.0 mm)	12000 Bar x °C
P x T Max. ( Thk 3.0 mm)	8500 Bar x °C
Leakage DIN 3535-6	<0.001 mg*s <sup>-1</sup> *m <sup>-1</sup>
Creep relaxation DIN 3535-6	<16 %
Compressibility DIN 3535-6	>50 %
Recovery DIN 3535-6	>5 %
Minimum PH	0
Maximum PH	14
Available sheets size	1.500x1.500 mm 1.750x1.750 mm
Available thickness	0.75 ÷ 6.00 mm
Sheet size tolerance	50 mm
Thickness tolerance	10 %



our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.