



### Product Specifications

**XGD 60** is a thermosetting plastic material reinforced with glass fiber.

### Material Specifications:

- Excellent compressive strength and outstanding insulating capability
- Continuous resistance to high temperatures
- Dimensional stability

### Fields of Application

**XGD 60** is primarily used in the mold and equipment manufacturing industry, where **dimensional stability and high-pressure resistance** are required.

### Supply Details:

- **Standard Thicknesses:** 4 – 30 mm
- **Premium Finish Available**
- **Thickness Tolerance:** +/- 0.02 mm on a nominal thickness of 0.02 mm

The values in this technical data sheet are standard values and are not part of any contract. Specifications may change depending on modifications in the operating environment.



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.

**Planichem s.r.l.**

Via Consolare 41/43 25030 Zocco di Erbusco (BS) - ITALY

Tel: +39 030 7386033 - [www.planichem.com](http://www.planichem.com) - [info@planichem.com](mailto:info@planichem.com)